


















BILL OF QUANTITIES





Sl. No.	Description	Unit	Dimension	Photo / Drawing	Qty	Qty for Kitchens in 27 Constituencies	Fuel / Power
GROSSERY BULK STORE							
1	PLASTIC PALLETS made out of high density plastic		48" x 40" x 6"HT		3	90	NA
DRY STORE ROOM							
2	SLOTTED ANGLE RACK - 5 SHELF (SLOTTED ANGLE BOLTLESS M.S. POWDER COATED STORAGE RACK) Key hole type vertical frame, WPC Board removable shelves placed over beams made out of 202 Grade stainless steel, anti rust and anti Magnetic		36" x 18" x 72" HT		10	300	NA
COLD ROOM							
3	COLD ROOM CHILLER FOR VEGETABLE 60mm PUF panel for wall and ceiling. PPGI inside and Outside. 50mm PUF slab insulation with vapor barrier for floor, (PCC with Kota by client). 01 set of 10000btu/hr refrigeration unit, R22 Refrigerant with aluminum sheet		8' x 8' x 8'HT		1	30	ELECTRICAL
4	SS STORAGE RACK - 5 SHELF 18g SS shelves double beeded on all sides, stiffed with 25 x 100 x 25mm hat channels, 38mm sq legs fitted with adjustable nylon bullet feets made out of 202 Grade stainless steel, anti rust and anti Magnetic		3'9" x 24" x 72"HT		4	120	NA






Sl. No.	Description	Unit	Dimension	Photo / Drawing	Qty	Qty for Kitchens in 27 Constituencies	Fuel / Power
5	SS STORAGE RACK - 4 SHELF 18g SS shelves double beeded on all sides, stiffed with 25 x 100 x 25mm hat channels, 38mm sq legs fitted with adjustable nylon bullet feets made out of 202 Grade stainless steel, anti rust and anti Magnetic		3" x 24" x 60"HT		1	30	NA
VEGETABLE CUTTING AREA							
6	SS STORAGE RACK - 5 SHELF 18g SS shelves double beeded on all sides, stiffed with 25 x 100 x 25mm hat channels, 38mm sq legs fitted with adjustable nylon bullet feets made out of 202 Grade stainless steel, anti rust and anti Magnetic		3'6" x 24" x 72"HT		1	30	NA
7	SS WORK TABLE WITH 1 UNDER SHELF 16g 304G SS top, 18g 304G SS under shelf, 38mm Sq. SS Legs fitted with adjustable nylon bullet feet with 4% nickel, anti magnetic food grade Stainless steel		60" x 24" x 34"+6"HT		3	90	NA
8	SS WORK TABLE WITH 1 SINK sink size 450 x 450 x 300mm deep, radius corners, 150mm rear splash, 16g 304G SS Sunk in top, 25mm dia SS pipe cross support, 38mm dia SS Legs fitted with adjustable nylon bullet feet with food grade stainless steel		60" x 24" x 34"+6"HT		1	30	NA

Sl. No.	Description	Unit	Dimension	Photo / Drawing	Qty	Qty for Kitchens in 27 Constituencies	Fuel / Power
GRINDING AREA							
9	WET GRINDER - TILTING MODEL Main Frame, Tilting Post & Arms is made up of Stain steel, Lid, Middle & Bottom Cover is made up of FRP, Bottom Body & Drum made up of stainless Steel 202Gr. Utility :Rice , Pulses, Masalas, Dhall ect.,		CAPACITY: 25 LTRS Motor Capacity 2 hp, Three ph., 415V, 50 Hz ph.,		3	90	ELECTRICAL
10	PULVERIZER CAPACITY: 3 HP Motor Capacity 2 hp, Three ph., 415V, 50 Hz ph., Body, Stand & Blades made of Stainless Steel.		CAPACITY: 3 HP Motor Capacity 2 hp, Three ph., 415V, 50 Hz ph.,		1	30	ELECTRICAL
11	COCONUT SCRAPPER- STAND TYPE Body & Stand made of Stainless Steel. Capacity: 50 to 60 Coconut / Hr. Approximate,		CAPACITY: 0.5 HP		1	30	ELECTRICAL
STEAM BOILER ROOM							
12	STEAM BOILER (LPG operated) 8mm inner shell, outer 6mm - 3 " & 4" tata class pipe, top 8mm verticle pipe 10mm flange set, MS Flout Box, SS Stand, Including Boiler Fittings it can be square or round.		CAPACITY : 100 KGS /HR (81 KW)		2	60	LPG

Sl. No.	Description	Unit	Dimension	Photo / Drawing	Qty	Qty for Kitchens in 27 Constituencies	Fuel / Power
STEAM COOKING AREA							
13	RICE COOKING STEAM VESSEL - GEAR TILTING MODEL (Single Jacketed): worm reduction gear tilting mechanism, VESSEL BODY : 3mm 304 grade SS, LID : 18 SWG 304grade SS SIDE HOUSING PANEL BOX : 18 SWG SS FRAME : The unit mounted on SS 75x25x4mm thick 'C' channels with brackets with rice strainers.		CAPACITY: 500 LTRS		2	60	STEAM
14	SAMBAR COOKING STEAM VESSEL - GEAR TILTING MODEL (Single Jacketed): worm reduction gear tilting mechanism, VESSEL BODY : 3mm 304 grade SS, LID : 18 SWG 304grade SS SIDE HOUSING PANEL BOX : 18 SWG SS FRAME : The unit mounted on SS 75x25x4mm thick 'C' channels with brackets.		CAPACITY: 350 LTRS		2	60	STEAM
15	IDLY STEAMER WITH STAND : Inner Chamber 16 SWG 304GRADE Outer Chamber 18 SWG 304grade, Including 1mm Idly Plates - 30 no's, Dip Tray-30nos, SS Stand, SS Bolt Net. Idli holding frame to come out completely		CAPACITY: 600 IDLIES		3	90	STEAM
16	Steam pipe line: 1" & 3/4" SS Pipe with SS 304 grade Ball Valve 1" 8 Nos, Flange, Clamp, Welding, Boldnet, Asbestor's, Labour Charge		Approx 100 RFT		100	3000	STEAM

Sl. No.	Description	Unit	Dimension	Photo / Drawing	Qty	Qty for Kitchens in 27 Constituencies	Fuel / Power
17	SS WORK TABLE WITH 1 UNDER SHELF 16g 304G SS top, 18g 304G SS under shelf, 38mm Sq. SS Legs fitted with adjustable nylon bullet feet.		48" x 24" x 34"HT		1	30	NA
BURNER COOKING AREA							
18	2 BURNER COOKING RANGE Top made out of 16SWG 304grade SS with 3 sides cover & front control panels, 2nos. 16" x 16" cast Iron grid with HP Burners & pilot burner, Control Valves, Connecting Pipes Spillage tray, verticals out of dia 1½" SS pipe Legs with adjustable nylon bullet feet's.		48" x 24" x 30"HT		1	30	LPG
19	STOCK POT BURNER Top made out of 16SWG 304grade SS with 3 sides cover & front control panels, 1no. 20" x 20" cast Iron grid with HP Burners & pilot burner, Control Valves, Connecting Pipes, verticals out of dia 1½" SS pipe Legs with adjustable nylon bullet feet's.		30" x 30" x 12" HT		3	90	LPG
20	WORK TABLE WITH 1 UNDER SHELF 16g 304G SS top, 18g 304G SS under shelf, 38mm Sq. SS Legs fitted with adjustable nylon bullet feet.		72" x 30" x 34"HT		1	30	NA

Sl. No.	Description	Unit	Dimension	Photo / Drawing	Qty	Qty for Kitchens in 27 Constituencies	Fuel / Power
POTS / VESSELS STORE AREA							
21	SS POT RACK - 4 SHELVES Main vertical Frame made out of 38mm dia SS pipes with horizontal frame made out of 32mm dia SS pipes with cross support 25mm dia SS pipes made out of 202 Grade stainless steel, anti rust and anti Magnetic		60" x 30" x 66" HT		4	120	NA
MATERIALS RECEIVING AREA							
22	WEIGHING SCALE WITH SS TOP		CAPACITY: 100 KGS		1	30	ELECTRICAL
23	2 SINK VEGETABLE WASHING UNIT sink size 450 x 450 x 300mm deep, radius corners, 150mm rear splash, 16g 304G SS Sunk in top, 25mm dia SS pipe cross support, 38mm dia SS Legs fitted with adjustable nylon bullet feet Top 304 grade 16 guage		60" x 24" x 34"+6" HT		1	30	NA
24	SS PLATFORM TROLLEY with 16g SS Top reinforced with Angle frame, 32mm dia x 16g SS Pipe Handle with Cross Suppot, Corner Guards, fitted with 4 Nos 125 mm Dia REXELLO heavy duty Hard Rubber wheels, 2 with brake and 2 without brake.		36" x 24" x 40" HT		2	60	NA

Sl. No.	Description	Unit	Dimension	Photo / Drawing	Qty	Qty for Kitchens in 27 Constituencies	Fuel / Power
25	SS DRAIN GRATING The modular grating will be made of SS L angle inserted with 20mm SS round pipe put together to make a grating grid, Separate Outer frame made of 304 SS grade L Angle with 3mm thick SS grouting support.		8" x 160 RFT		160	4800	NA
EXHAUST SYSTEM							
26	Supply of centrifugal blower having capacity of 2900 cfm at 60mm static pressure to suit 3 hp/1440 r.p.m,415 volts, 3 ph ISI motor.Motor make: CROMPTON GREAVES/ KIRLOSKAR		3 HP / 1440 rpm,		2	60	NA
27	Supply of Fume Exhaust hood made out of Stainless steel 202 Grade 20 SWG along with grease filters. WALL TYPE HOOD:		17 feet x 3'6" x 20"HT		1	30	NA
28	Supply of Fume Exhaust hood made out of Stainless steel 202 Grade 20 SWG along with grease filters. WALL TYPE HOOD:		14 feet x 30" x 20"HT		1	30	NA
29	Supply of GI ducting made out of GI Sheets 22/24 SWG along with flanges for blower inlet and outlet connection		(Approx 600 Sq.Ft)		600	18000	NA

Sl. No.	Description	Unit	Dimension	Photo / Drawing	Qty	Qty for Kitchens in 27 Constituencies	Fuel / Power
	OTHER ITEMS						
30	Gas Line Installation: 4 Cylinder manifold With ½” TATA C- Class ERW pipe, Fittings like Connecting Valves, Pipes, Flexible, Pinset, Clamps, Regulator Adopter, Manifold, labour & Installation Charges.		APPROX 120 RFT		120	3600	NA
31	Insect Killer		Stainless steel Equipment		4	120	ELECTRICAL
	FOR TRANSPORTATION ITEMS						
32	25 ltrs of Stainless steel milk pot				2	440	NA
33	Stainless steel trays with handles				6	1300	NA
34	Marmite 50 guage capacity				210	1760	NA